

CHC Chiller Compact Series

Compact Modules In An Enclosed Design



Marine Air's Chiller Compact series is ideal for larger boats in the 45-70 ft. (15-20 m) range. Available in capacities ranging from 16,000 to 24,000 BTU/hr, the Chiller Compact uses circulated water in a closed loop in place of copper refrigerant tubes. The innovative, space-saving compact base of the Chiller Compact was designed to allow individual modules to be multiplexed to provide precise capacity requirements for any application.

Featuring high-efficiency components that offer maximum performance, the Chiller Compact uses rotary or scroll compressors which are quieter and consume less power. A custom-fabricated condenser coil is constructed of spiral-fluted cupronickel to provide maximum heat transfer and high corrosion resistance.

The environmentally friendly, hermetically-sealed Chiller Compact units use closed-refrigerant circuits, pre-charged with refrigerant. No additional refrigerant is required during the installation or at initial start-up and operation of the system.

Key Benefits

- Compact footprint for installation flexibility.
- Single modules can produce up to 26,400 BTU/hr.
- Up to six modules can be multiplexed for larger capacities.
- Thermodynamically-matched components assure maximum performance.
- High-efficiency rotary or scroll compressors.
- Fewer moving parts ensure better reliability.
- Spiral-fluted cupronickel condenser coil provides maximum heat transfer and corrosion resistance.
- Digital Diagnostic Controller (DDC) monitors and protects the system.
- Charged, tested, and leak checked at the factory.
- Meets or exceeds all applicable standards and regulation.
- Charge Guard protection provides sealed access ports, ensuring environmental protection and chiller module integrity.

Specifications for CHC Chiller Compact Series

Model ⁽¹⁾	CHC16	CHC20	CHC24
Capacity (Btu/h)	16000	20000	24000
Voltage (V)	115	220	230
Cycle (Hz)/Phase (Ph)	60/1	50/1	50/1
Kilo-Volt-Amps (kVA)	1.24	1.36	2.00
Refrigerant Type	407C	407C	407C
Max. Height (in/mm) ⁽²⁾	12.7/324	15.75/401	15.75/401
Max. Width (in/mm) ⁽³⁾	11.5/293	13.331	13.331
Max. Depth (in/mm) ⁽²⁾	18.458	18.458	18.458
Seawater Connection (in/mm)	5/8/16	5/8/16	5/8/16
Net Weight (lbs/kg) ⁽⁴⁾	52/23.6	58/26.4	84/38.2
Gross Weight (lbs/kg) ⁽⁴⁾	63/28.2	68/30.9	94/42.7


¹ Add a 7'230V/60Hz units or 7'50' for 220V/50Hz units.

² All dimensions \pm 0.25 in. (6 mm).

³ Add 1.0 in. (26 mm) to width or depth for mounting brackets, depending on their rotation.

⁴ All weights \pm 10%.

Dimensions



DOMETIC MARINE DIVISION
2000 N. Andrews Ave. | Pompano Beach, FL 33069 USA | Tel: 954-973-2477 | Fax: 954-979-4414
www.Dometic.com/Marine | MarineSales@DometicUSA.com

24/7 TECH SUPPORT FOR UNITED STATES & CANADA:
8:00 AM to 5:00 PM Eastern Time: 800-542-2477
After hours and weekends: 888-440-4494

INTERNATIONAL SALES & SERVICES
Europe & the Middle East: Call +44(0)870-330-6101
For all other areas visit our website to find your nearest distributor.

L-2135 Rev. 20120824
Specifications and availability subject to change without notice.

Dealer

