2307 & 2308 AC High AMP Main Circuit Breaker Panels

2307 AC High AMP Main Circuit Breaker Panel (Two Pole Main Breaker)

GENERAL FEATURES & BENEFITS

- Completely pre-wired to reduce installation time
- Panel is 1/8" corrosion resistant aluminum coated with two-part polyurethane
- Hydraulic/magnetic, trip free Circuit Breakers. UL recognized (UL-1077).
- Voltage and Shore Cord Current: 30 AMPS, 120 VAC-60 HZ USA is standard. Other ratings voltages and frequencies - optional.
- Main Breakers: 30 AMPS is standard. 16, 40, 50, 60, 80 and 100AMPS optional. Mains provide 5000 AMPS Interrupt capacity rating.
- Dimensions: 5 1/2" W X 8 1/4 " H X 3 3/4 " D.
- Color: Black is standard. Optional: White, Gray and Beige.

2308 AC High AMP Main Circuit Breaker Panel (Three Pole Main Breaker)

GENERAL FEATURES & BENEFITS

- Completely pre-wired to reduce installation time
- Panel is 1/8" corrosion resistant aluminum coated with two-part polyurethane
- LED Indicators provided on all Premier Line Panels
- Hydraulic/magnetic, trip free Circuit Breakers. UL recognized (UL-1077).
- Voltage and Shore Cord Current: 50 AMPS, 240 VAC-60 HZ USA is standard. Other current ratings, voltages, and frequencies OPTIONAL.
- Main Breakers: 50 AMPS standard. Also available on 40, 50, 60, 80 and 100 AMPS. Main breakers providing 5000 AMPS Interrupt capacity rating.
- Dimensions: 5 1/2 "W X 8 1/4 " H X 3 3/4" D.
- Color: Black is standard. Optional: White, Gray and Beige.







